

Class 3000

GM ECOTEC POWERED 4-CYL PRODUCTION MOTOR, SHORT WHEELBASE

Two seat open wheeled mini cars, and two seat mini trucks. VEHICLES MUST HAVE TWO (2) OCCUPANTS.

COMPETITION REGULATIONS

This is an open class and all components will be considered open unless it says otherwise in these rules.

TRANSAXLE EQUIPT VEHICLES NOT EXCEED 103" WHEELBASE AS MEASURED AT RIDE HEIGHT.

LIVE AXLE EQUIPT VEHICLES NOT TO EXCEED 111" WHEELBASE AS MEASURED AT RIDE HEIGHT.

ENGINE, TRANSMISSION AND DRIVELINE

Engine and Engine Displacement

Engine location is open. Engine is limited to stock production GM Ecotec 4 cyl. 2.2 and 2.4 motors. Pistons must be stock or stock replacement pistons must retain stock dimensions. Camshaft must be stock or equal replacement only. Camshaft must retain original manufacture specifications. Head / valve train must remain per manufactures original specifications. After Market valve train is prohibited, no porting or polishing of head. Must retain manufactures original specifications. Intake manifold will remain as delivered from manufacture. It must retain its stock shape, size and configuration. No porting or other modifications will be allowed. Throttle body will remain as delivered from the manufacturer, not to exceed 65mm on blade. No dry sump systems allowed.

All stock production engines are to be inspected and sealed by TURNKEY ENGINE SUPPLY, WIKS RACING ENGINES, REDLINE PERFORMANCE, MAJOR PERFORMANCE OR CBM to be certified as stock replacement.