

MORE 1600 Outlaw – 1600X (Updated 2025)

This class is an open class and all components will be considered open unless restricted herein

Engine:

Option 1

- Stock Sealed 1.5 Honda Fit Engine (L15A7)
- ECUs Permitted:
 - Stock
 - AEM EMS 4
 - Holley
 - Link Monsoon or Link Fury
- Wiring Harness Open
- Throttle Body
 - Stock drive by wire allowed
 - GM 50mm manual throttle body with adapter
- No internal modifications allowed.
- No aftermarket oil pans, no dry sump.
- No Forced Induction.
- Headers / Exhaust Open .

Option 3

- Current legal MORE 1600 high comp engine

Option 4

- Current legal MORE 1600 low comp engine

Tranny:

- Any 4 Spd H Pattern, non sequential, transmission (091, 094, mendeola 2d, weddle HV1)
- Must have working reverse gear.

Max Track Width front and rear:

- 60" Measured from wheel mounting face to wheel mounting face measured at ride height. (Current 1600: Front 55.75"max, Rear 58.25" max)

Front Suspension:

- Any front suspension (A-Arm, Beam...)
- 60" max width as stated above.
(Stock VW Beam with 2" wider arms: 59.75")

Rear Suspension:

- Any rear suspension
- 60" max width as stated above.
- Coilover or torsion permitted.
- No outboard or midboard hubs, The entire outer CV must remain inboard of the trailing arm inner bearing.

Minimum weight:

- single seat TBD
- two-seat TBD